

Приложение П - Срокове към Общи условия на The Sales House / Appendix П - Deadlines to General Sales Rules of The Sales House

Срокове за подаване на заявки и рекламни материали / Deadlines for sending orders and advertising materials

Ден:	Да се изпрати за:
понеделник	петък, събота
вторник	неделя, понеделник
сряда	вторник
четвъртък	сряда
петък	четвъртък

On Day	To be sent for:	
Monday	Friday, Saturday	
Tuesday	Sunday, Monday	
Wednesday	Tuesday	
Thursday	Wednesday	
Friday	Thursday	

Спонсорски заставки за Євроспорт - 7 дни преди излъчване / Sponsorship tags should be sent 7 days before first airing Материали за RakutenTV - 5 дни преди излъчване/ RakutenTV materials - 5 days before first airing

\* При официални празници, изтеглените срокове ще се изпращат допълнително, уточнени за всеки канал / Special deadlines for holidays/non-working days will be sent for each channel

Приложение П 2 – Технически изисквания към Общи условия на The Sales House / Appendix П 2 – Technical requirements to General Sales Rules of The Sales House

Всички файлове трябва да бъдат с пълни секунди до 24 кадъра! / All files should be delivered with full seconds up to 24 frames! Всеки файл за Nick канали трябва да бъде придружен с превод на озвучаването на английски / All files for Nick channels should have an attachment with English translation of the VO





	HD Delivery Specifi	cation for AdStream		
	Apple ProRes 422HQ 1080/50	MXF Wrapped XDCAM 108050	MPEG-2 Transport Stream 1080/50	
	Vi	deo		
Codec	Apple Quicktime ProRes 422 (HQ)	XDCAM 422	MPEG-2	
Container	mov	MXF	MPEG-2 Transport Stream	
Profile	HQ	MPEG-2 422P@HL	422P@HL	
litrate		50Mb/s CBR	100Mb/s CBR	
hroma Subsample		4:2:2		
nterlacing		Upper/Tff		
OP Structure		Long GOP	I Frame Only	
rame Size	1920x1080			
rame Rate		25 FPS		
Ispect Ratio		16:9		
	Video Level I	Requirements		
V Format : HDTV				
Ispect Ratio : 16:9				
itle Safe : 16:9 as per EBU R.95-1				
All Video Signals Should Comply U	Jith ITU-R			
BT.709-5 And Video Signals Should				
	OmV, Or Fall Below OmV Out of gamu	t tolerance		
	ters will reject illegal video levels th		nces where it is difficult	
	EBU recommendation Rec.103-2000			
han 1% of the active picture is in e				
uminance (Y) -1% and 103% (ie betu				
2GB video levels -5% and 105% (ie				
0) 1000 1010 000 0000 0000		ıdio		
Codec	PCM (Little Endian)	PCM (Big/Little Endian)	PCM	
Sample Rate	r om (ercao enoion)	48kHz	1 5	
Sample Size		24bit		
Channels		Stereo		
	Audio Level	Requirements		
Denending on the final destination	, the SCE region accepts audio mixe			
PPM / Max Peak	, 110 000 109,011 0000p10 00010 111110	5 55 51 41 51 .		
Permitted Max Level: PPM 6 (-10dB	f\$]			
Alignment Level: 1kHz@ -18dBFS	10)			
Ballistic: PPM Type IIa as per IEC 60	1268 IN			
Refer to EBU R68-2000 for guidanc				
Files should always be R128 EBU R.1				
ntergrated Loudness Program: -23				
arget Level Tolerance: +/- 0.5 LU	turs			
Namum True Peak : -3dBTP				
Maximum Momentary: -15 LUFS				
Sector Library Late of the control of		dio Guidance:		
	ak ('R68'/PPM) ca be converted to n			
	ng from R128 to 'R68'/max peak, as t		ow audio levels.	
unere required this will be normal	lised to meet the correct program lo			
		Post Roll Information		
Ouration	Example Timecode			
30"	00:00:00:00 - 00:00:29:24			
File naming should be. ClockNumber_Product or Product_Title_Duration_Audio				
The clock number on the order must contain a maximum of 20 characters				
t is advised to use the layout <b>BBB</b> -	-PPPNNN-DDD where:			
B : Brand/Agency				
P : Product				
N : Unique Sequential ID Number				
D : Duration				

Discovery Channel, TLC, ID, HGTV, Eurosport 1, Travel Channel, Cartoon Network,				
Cartoonito, Nickelodeon, Nick Jr., Nicktoons, ducktv, BG On Air				
General				
Wrapper	ОР1а			
File Extension	.mxf (Closed/Complete)			
Video Track				
Codec	XDCAM HD422			
Colour Sampling	04:02:02			
Bitrate	50Mbps (CBR)			
GOP	Long GOP			
Bit depth	8 bits			
Resolution	1920 X 1080			
Aspect Ratio	16:09			
Interlaced	yes			
Frame rate	25 fps			
Field dominance	Top Field First (TFF)			
Luminance Levels	0mV to 700mV			
Luminance Tolerance (EBU R103-2000)	-1% to 103%			
Audio tracks				
Number of Audio Tracks/Pairs	1			
Number of channels per Track	2			
Codec	PCM			
Sample Rate	48kHz			
Bit depth	24			
Endianess	Little			
Target Loudness (EBU R128)	-23LUFS (±0.5 LU)			
Мах Permitted True Peak Level (EBU R128)	1 dBTP			
Timecode track				
Timecode standard	SMPTE			
First frame TC	00:00:00:00			

RakutenTV - for appearance on CTV devices and Web and Mobile			
General			
File Extension	.mp4		
3rd Party tracking tags	If not - by WeTransfer		
Video Track			
Container/ Codec	MP4/H264		
	H264 main profile, H264 level <= 3.0		
Ріхеl Format	YUV 4:2:0		
Maximum Duration	30 seconds		
Bitrate	4-5 Mbps(FHD)		
	3.5 Mbps (HD)		
Resolution	1920 X 1080 (1080p)		
Aspect Ratio	16:09		
if not possible	> 16:09 (by ffmpeg SAR)		
	1:1 source aspect ratio (by ffmpeg SAR)		
Frame rate	25 fps		
Audio tracks - required			
	192 kbps minimum		
Number of channels per Track	2		
Codec	PCM or ACC		
Sample Rate	AAC-LC up to 48 kHz		
Bit depth	16 or 24 bit only		
Design and Other			

Letterboxing burnt bars or pillarboxing are not accepted Video must be submitted without leaders (i.e. slates, countdowns) Material should be dubbed in Bulgarian or subtitles to be used